



HYDRO GE Series

450W / 550W / 650W

Introduction

Hydro GE 80 Plus[®] Gold Power Supply is designed to maximize cooling efficiency with features such as a 135mm FDB fan with thermal control design, internal component arrangement for increased airflow, enhanced heat dissipation and efficient energy conversion. This Hydro GE series also features changeable logos that allow DIY enthusiasts to match the logo with the rest of the hardware.

Features



Full Modular Easy Installation, neat build

	Т	Г]
	Τ	Τ	Ī
	-		

Ribbon Cable Easy Installation, neat build





Quiet and Durable Cooling FDB(Fluid Dynamic Bearing) fan with low noise and long-lasting life span

- · Complies with ATX12 v2.4 & EPS12 v2.92
- High efficiency \geq 90%
- · Active PFC ≥ 0.9
- · 80PLUS® Gold certified
- · Changeable side stickers for DIY enthusiasts and gamers
- · +12V Single-rail design
- · Full modular with ribbon Cables
- · Full Japanese electrolytic capacitors
- · Supports 6+2 pin PCI-Express connectors
- · Quiet and long-lasting 135mm FDB fan
- · Complete protections: OCP, OVP, SCP, OPP, UVP, OTP
- · Global safety approved




HYDRO GE Series

Product Overview

Pro Hydro Ge





Both of +3.3V and +5V DC – DC module combined +12V SR circuit offers supreme efficiency, voltage stability and high system compatibility especially in cross regulation(unbalance load) mode.

Full Modular Design with Ribbon Cable

Neat build and easy installation, enhance cooling performance.






100% Japan-made E-Cap Japan-made electrolytic capacitors endure over 100° C degree temperature, it ensures safety on spare parts for prolong lifespan and reliability.

Special Cooling Design for 12V Circuit

12V circuit offers most power to key components such as VGA and it generates heat easily to affect performance. An advanced 12V cooling design to dissipate heat quickly and keep PSU in optimal cooling environment.





Product Overview


Choose Your Logo

The FSP Hydro GE series features changeable logos. DIY Enthusiasts can choose either a blue, red or green logo to complement the rest of the system hardware. Out of the box, the logo is blue. Builders can apply either a red or green sticker over the original blue logo to fit their preferences.



FSP HYDRO GE Series

Performance





FSP HYDROGE Series 450W / 550W / 650W

Rating

450W	AC Input	100-240Vac~ 8-4A 60-50Hz				
	DC Output	+3.3V	+5V	+12V	-12V	+5Vsb
	Max Output Current	20A	20A	37.5A	0.3A	2.5A
	Max Combined Power	100)W	450W	3.6W	12.5W
	Total Power	450W				
550W	AC Input	100-240Vac~ 8-4A 60-50Hz				
	DC Output	+3.3V	+5V	+12V	-12V	+5Vsb
	Max Output Current	20A	20A	45.84A	0.3A	2.5A
	Max Combined Power	100W		550W	3.6W	12.5W
	Total Power	550W				
650W	AC Input	100-240Vac~ 10-5A 60-50Hz				
	DC Output	+3.3V	+5V	+12V	-12V	+5Vsb
	Max Output Current	20A	20A	54.16A	0.3A	2.5A
	Max Combined Power	120W		650W	3.6W	12.5W
	Total Power	650W				



FSP HYDROGE Series 450W / 550W / 650W

Specifications

	A HANDON OF	Hudo or Antonio	No. OF
	450W	550W	650W
Model	HGE450	HGE550	HGE650
Туре	ATX	ATX	ATX
PFC	Active PFC	Active PFC	Active PFC
Input Voltage	100V-240V	100V-240V	100V-240V
Input Current	8-4A	8-4A	10-5A
Input Frequency	60-50Hz	60-50Hz	60-50Hz
Output Capacity	450W	550W	650W
Max. Output Power	450W	550W	650W
Fan Type	FDB Fan, 135mm	FDB Fan, 135mm	FDB Fan, 135mm
Efficiency	90%	90%	90%
MTBF	100,000 Hrs	100,000 Hrs	100,000 Hrs
Protection	OCP, OVP, OPP,	OCP, OVP, OPP,	OCP, OVP, OPP,
	SCP, UVP, OTP	SCP, UVP, OTP	SCP, UVP, OTP
Weight			
Dimension(L×W×H)	150 × 170 × 86 mm	150 × 170 × 86 mm	150 × 170 × 86 mm




Connectors

	450W	550W	650W
	1	1	1
20+4 PIN			
	1	1	1
4+4 PIN			
	2	4	4
6+2 PIN			
	6	8	12
SATA			
	1	3	3
MOLEX			
	1	1	1
FLOPPY			



Cable Length


450W





Cable Length


550W





Cable Length

650W





FSP HYDROGE Series 450W / 550W / 650W

Package Information

Model	HGE450	HGE550	HGE650
EAN Code	471322452073 0	471322452074 7	471322452075 4
UPC Code	84568500948 7	84568500949 4	84568500950 0
Shipping Dimensions (L×W×H)	327 × 245 × 96 mm		
Shipping Weights			
Master Pack Dimension (L×W×H)	540 × 275 × 351 mm		
Master Pack Quantity	5 retail boxes per master package		
Master Pack Weight			
Pallet Quantity	200 (5 retail boxes × 40 master boxes)		
Country of Origin	China		
Warranty	5 Years		
Additional Information			