

### GRAPHICS CARDS Radeon™ RX 6400 AERO ITX 4G







### **SPECIFICATIONS**

Model Name	Radeon™ RX 6400 AERO ITX 4G
Graphics Processing Unit	Radeon™ RX 6400
Interface	PCI Express <sup>®</sup> Gen 4 x 4
Core Clocks	Boost: Up to 2321 MHz Game: Up to 2039 MHz
CUDA <sup>®</sup> CORES	768 Units
Memory Speed	16 Gbps
Memory	4GB GDDR6
Memory Bus	64-bit
Output	DisplayPort x 1 (v1.4a) / HDMI <sup>™</sup> x 1 (Supports 4K@120Hz/8K@60Hz and VRR as specified in HDMI <sup>™</sup> 2.1)
HDCP Support	<u>Y</u>
Power consumption	53W
Power connectors	Ν/Α
Recommended PSU	350W
Card Dimension (mm)	172 x 112 x 39 mm
Weight (Card / Package)	358g / 718g
DirectX Version Support	12 API
OpenGL Version Support	4.6
Maximum Displays	2
VR Ready	<u>Y</u>
FreeSync™ Technology	Y
<b>Digital Maximum Resolution</b>	7680 x 4320

# CONNECTIONS



## **FEATURES**



#### Custom PCB

The custom PCB has been engineered with hardened circuits and optimized trace routing for performance and reliability.

### Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.

#### Thermal Padding



An abundance of thermal pads use any chance for additional heat transfer directly from the components.

#### MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

'Boost Clock Frequency' is the maximum frequency achievable on the GPU running a bursty workload. Boost clock achievability, frequency, and sustainability will vary based on several factors, including but not limited to: thermal conditions and variation in applications and workloads. 'Game Frequency' is the expected GPU clock when running typical gaming applications, set to typical TGP (Total Graphics Power). Actual individual game clock results may vary. © 2023 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.